



A.R.I. Flow Control Accessories Ltd. provides expertise in the planning, development and implementation of advanced solutions for system protection from transient pressures, entrapped air in pipelines and unmeasured non-revenue water.

These solutions are accomplished with the design, development and manufacture of valves and accessories for fluid piping systems as well as the resources required to execute an in-depth analysis of these systems for implementing proper air valve sizing and location.

A.R.I., while addressing the ever changing needs of the market place, pledges to uphold

- A high standard of quality
- A commitment to service and training
- Diligence in innovation and development
- Design of long-lasting products with minimal maintenance



VALVES FOR AGRICULTURAL SYSTEMS



A.R.I. FLOW CONTROL ACCESSORIES Ltd.
www.arivalves.com ari@ari.co.il Tel: 972-4-6761988

0305-EnBrsAGR-17



Where Knowledge & Experience join with Innovation

D-43
Combination Air Valve "Barak Pro"

2" / 50mm
0.05 - 10 bar (0.7 - 150 psi)
0.1 - 16 bar (2-250 psi)



DG-70
Dynamic Combination Air Valve

2" / 50mm, 3" / 80mm - Threaded / Flanged
4" / 100mm - Flanged
0.2 - 10 bar (3-150 psi)



DG-10 / D-040
Combination Air Valve "Barak"

1/2" / 15mm, 3/4" / 20mm, 1" / 25mm, 2" / 50mm
Threaded / Flanged
DG-10 0.1-10 bar (2-150 psi)
D-040 0.2-16 bar (3-250 psi)
D-040 LP 0.05 - 6 bar (0.7 - 87 psi)



D-021
Mini Combination Air Valve
for Raw & Reclaimed Water

1" / 25mm, 2" / 50mm
Threaded / Flanged
0.2 - 10 bar (3-150 psi)



D-040 L
Combination Air Valve "Barak"

1/2" / 15mm, 3/4" / 20mm, 1" / 25mm, 2" / 50mm
0.02 - 10 bar (0.3 - 150 psi)
0.05 - 16 bar (0.7 - 250 psi)



S-021
Mini Automatic Air Release Valve
for Raw & Reclaimed Water

1" / 25mm, 2" / 50mm
Threaded / Flanged
0.2 - 10 bar (3-150 psi)



DT-040
Combination Air Valve with
Orifice Shut-off Valve "Micro Barak"

1/2" / 15mm, 3/4" / 20mm - Threaded
0.2-10 bar (3-150 psi)



SG-10 / S-050
Automatic Air Release Valve

1/2" / 15mm, 3/4" / 20mm, 1" / 25mm - Threaded
SG-10 0.1 - 10 bar (2-150 psi)
S-050 0.2-16 bar (3-250 psi)



DT-040 LP
"Micro BARAK" for Low Pressure
Combination Air Valve with
Orifice Shut-off Valve

1/2" / 15mm, 3/4" / 20mm - Threaded
0.05-6 bar (0.7-87 psi)



S-050 L
Automatic Air Release Valve

1/2"/15mm, 3/4" / 20mm 1"/25mm
0.02 - 10 bar (0.3 - 150 psi)
0.05 - 16 bar (0.7 - 250 psi)



AV-010
Air & Vacuum Valve

3/4" / 20mm, 1" / 25mm, 2" / 50mm, 3" / 80mm
Threaded
0.2-10 bar (3-150 psi)



NR-040 FS
Check Valve
for Raw & Reclaimed Water

4" / 100mm - 40" / 1000 - Flanged
16 bar (250 psi) / 25 bar (360 psi) / 40 bar (580 psi)



NR-010
Wafer Style Check Valve

1 1/2" / 40mm - 10" / 250mm
10 bar (150 psi) / 16 bar (250 psi)



Eliptix R-20 Series
Diaphragm Hydraulic Control Valve

1 1/2" 40 mm - 8" / 200 mm
Threaded / Grooved / Flanged
/ Solvent welding / Union (SW)
0.2 - 10 bar (3-150 psi)



Eliptix R-30 Series
Diaphragm Hydraulic Control Valve

1" / 25mm - 16" / 400 mm
Threaded / Grooved / Flanged
0.2 - 10 bar (3-150 psi)
0.2-16 bar (3-250 psi)



Eliptix Control Pilot Valve

2 Way or 3 Way Control Pilot Valve
Metal / Reinforced Nylon
0.2-16 bar (3-250 psi)

